

See the detail on the back !

Safe, secure couplings TOYOCONNECTOR® TC3-F Cap nut FERRULE types

\bigcirc Can prevent troubles during production

- · Prevention of foreign matter intrusion or odor transfer and reduction of product loss through piping identification
- \cdot Fluid leakage and hose disconnection are less likely to occur, reducing problems and maintenance.
- \bigcirc Food safety
- The nipple shape that suppresses fluid accumulation is sanitary
- \bigcirc Standardization of work and reduction in hose installation
 - · It is easy to insert. Anyone can install it securely.
- Reduction of waste
 - \cdot As the body is reusable, waste and cost can be reduced.
- \bigcirc For assisting countermeasures against disaster risks
 - · Resistant to vibration, hard to come off and can recover quickly after disasters such as earthquakes.

Specification Material : stainless steel (MRD) Composition of sanitary structure + Leak and disconnection prevention structure + Easy-to-insert structure



* Hybrid products refer to highly functional products realized through the combination of technologies for "lamination", "reinforcement", and "connection".

▲ Caution The resin rings may change color, deteriorate or become damaged if they come into contact with fluid, depending on the type of fluid. Please replace the rings if you become aware of any abnormalities.

A Caution Suitable pressures and temperature ranges upon installation of hoses are dependent on the performance of the hoses.

Replacement sleeve set with gasket for TOYOCONNECTOR TC3-F * Material Sleeve : Polyacetal , Packing : Silicone Rubber

| | Code | Applicable TOYOCONNECTOR |
|--|-------------|--------------------------|
| | TC3-F15-RSS | TC3-F15Type All types |
| | TC3-F19-RSS | TC3-F19Type All types |
| | TC3-F25-RSS | TC3-F25Type All types |

□ Replacement resin ring for TOYOCONNECTOR TC3-F type

* Material Resin ring : Polyacetal

TOYOX CO..LTD. **JAPAN**

ISO 14001 certified

Packaging unit

> 10 <mark>10</mark> 10

| | Code | Applicable TOYOCONNECTOR | Packaging unit |
|--|-------------------------|--------------------------|-------------------|
| | TC3-F15-PO(BL/RD/YE/GR) | TC3-F15-1S-(BL/RD/YE/GR) | 1 |
| | TC3-F19-PO(BL/RD/YE/GR) | TC3-F19-1S-(BL/RD/YE/GR) | 1 |
| | TC3-F25-PO(BL/RD/YE/GR) | TC3-F25-1S-(BL/RD/YE/GR) | 1 |

Complete Hose Solution

% Resin rings cannot be mounted on TC3-F types without resin rings.



Subject to modification without notice
Color of product shown may differ from that of actual product due to limitations of printing.